

CHAPTER 2: SOFTWARE DESIGN WITH THE UNIFIED MODELING LANGUAGE


SESSION III: UML BEHAVIORAL MODELING

Software Engineering Design: Theory and Practice

by Carlos E. Otero

Slides copyright © 2012 by Carlos E. Otero

For non-profit educational use only



May be reproduced only for student use when used in conjunction with *Software Engineering Design: Theory and Practice*. Any other reproduction or use is prohibited without the express written permission of the author.

All copyright information must appear if these slides are posted on a website for student use.

SESSION'S AGENDA

- UML behavioral modeling
 - ✓ What is behavioral modeling?
 - ✓ Why is it important?

- Use case diagrams
 - ✓ Actors
 - ✓ System boundary
 - ✓ Common relationships

- Interaction diagrams
 - ✓ Communication diagrams
 - ✓ Sequence diagrams
 - ✓ Concurrency modeling

- Summary and conclusion of UML coverage

UML BEHAVIORAL MODELING

- In the previous session, we presented structural modeling and made a case for how it is essential to evaluate, characterize, and visualize the structural design of software systems from various perspective. Specifically, we presented:
 - ✓ Logical structural designs
 - At different levels of abstraction
 - ✓ Physical structural designs
- We also presented (very vaguely) the concept of **Quality** and discussed how structural modeling can be used to evaluate and access quality in terms of some quality goals, such as *reusability* and *maintainability*.
- Although structural designs work well for evaluating some quality attributes of systems, they are inadequate for others, such as *performance*.
 - ✓ Structural designs also provide poor techniques for evaluating the dynamic aspects and interactions of systems.
- UML provides several diagrams to model and reason about the dynamic aspects and of systems.
 - ✓ These can be used to model almost any behavioral aspect of modern software systems
 - ✓ They are used in many practical development projects.

UML BEHAVIORAL MODELING

- From previous sessions, we learned that the most common UML *behavioral diagrams* include:

Behavioral Diagram	Description
Use Case Diagram	Used to capture, specify, and visualize required system behavior .
Sequence Diagram	Used to capture, specify, and visualize system interactions with emphasis on the time-order sequence of messages exchanged.
Communication Diagram	Used to capture, specify, and visualize system interactions with emphasis on the structural order of entities participating in the message exchange.
State Machine Diagram	Used to capture, specify, and visualize system behavior as a set of discrete states and the transitions between them.
Activity Diagram	Used to capture, specify, and visualize system behavior; provide mechanisms for modeling that includes conditional statements, repetition, concurrency, and parallel execution and thus can be used at many different levels of abstraction, from modeling business work flows to code.

- Other behavioral diagrams include:
 - ✓ Timing diagram
 - ✓ Interaction overview diagram

UML BEHAVIORAL MODELING – USE CASE DIAGRAM


- Use case diagram
 - ✓ Behavioral diagram used to capture, specify, and visualize required system behavior.
 - Required system behavior are just requirements!
 - ✓ The main elements of use case diagrams are *actors*, *use cases*, and the *relationships* connecting them together.

- Actors are entities used to model users or other systems that interact with the system being modeled (i.e., the subject). Examples include:
 - ✓ Operators
 - ✓ Sensors
 - ✓ Client computers

- Use cases are entities used in use case diagrams to specify the required behavior of a system.
 - ✓ They provide the means to capture, model, and visualize the systems' required behavior.
 - ✓ They do this without any knowledge of programming technology, so that different stakeholders with different backgrounds can reason about the system.


UML BEHAVIORAL MODELING – USE CASE DIAGRAM

- Common UML relationships applied in use case diagrams.




Important:
include relationship specifies a mandatory inclusion
Extend relationship specifies an optional inclusion

UML BEHAVIORAL MODELING – USE CASE DIAGRAM



This models the behavior of a client system. An Operator and Server both interact with the Client System, denoted by the System Boundary.

UML BEHAVIORAL MODELING – USE CASE DIAGRAM



UML BEHAVIORAL MODELING – INTERACTION DIAGRAMS

- Interaction diagrams can be used to model complex interactions between design units together with the messages exchanges and the type of the exchange.
- Interaction diagrams can be used at the architectural level.
 - ✓ For example, they allow us to model interaction among software components.
- Interaction diagrams can be used at the detailed design level.
 - ✓ For example, they allow us to model interactions among objects at run-time
- Interaction diagrams can be used at the construction design level.
 - ✓ For example, they allow us to model conditional and repetition structures.
- In many situations, interaction diagrams reveal many important issues related to the quality of the system.
- Two types of interaction diagrams are:
 - ✓ Communication diagrams
 - ✓ Sequence diagrams

UML BEHAVIORAL MODELING – COMMUNICATION DIAGRAM


- Communication diagrams
 - ✓ Behavioral diagrams used to capture, specify, evaluate, and visualize system interactions with emphasis on the structural order of entities participating in the message exchange.

- When using communication diagrams, entities can be modeled as
 - ✓ Objects, representing instances of classes and components.
 - ✓ Roles, representing a prototypical instance

- Both objects and roles can be connected to model the exchange of messages using:
 - ✓ Links to connect objects
 - ✓ Connectors to connect roles
 - ✓ Both links and connectors look exactly alike, as a solid line. They only differ semantically.


- The type of message exchanges include:
 - ✓ Asynchronous
 - ✓ Synchronous

UML BEHAVIORAL MODELING – COMMUNICATION DIAGRAM



UML BEHAVIORAL MODELING – COMMUNICATION DIAGRAM


Communication diagram of objects at run-time using synchronous messaging



Given this model, can "cm" begin other operations before the file system format is complete?

UML BEHAVIORAL MODELING – SEQUENCE DIAGRAM

- Sequence diagrams
 - Similar to Communication diagrams, but, they put emphasis on the time-order sequence of messages exchanged.




UML BEHAVIORAL MODELING

➤ Finally, a word about concurrency...

SystemManager process, located on client PC does not have to wait until Sensor Nodes are powered on to begin doing other work

Asynchronous messaging

Synchronous messaging



We use Active Objects to model independent flows of control, e.g., processes.

We use stereotype <<process>> to specify these are actual run-time processes.

We use Tagged values to specify the location of the running processes.

SiteManager works in lock-step with nodeOne. Once nodeOn is powered on, then SiteManager initiates power on sequence of nodeTwo

WHAT'S NEXT...

- Now that we are equipped with the necessary UML tools, we can now explore how to use them to design a software architecture.
- In the next session, we will present Software Architecture in more detail, including :
 - ✓ Understanding the role of software architecture within the design phase.
 - ✓ Explore in more detail the architectural tasks and problem-solving during architecture.